

Technische Daten OptiSpheric®

	OptiSpheric® Auto Focus 500 automatische Messung	OptiSpheric® Auto Focus 1000 automatische Messung	OptiSpheric® Auto Focus 1500 automatische Messung	OptiSpheric® Auto Focus 2000 automatische Messung
Linsendurchmesser	3 mm ... 35 mm optional: 5 mm ... 75 mm	5 mm ... 75 mm optional: 3 mm ... 35 mm	5 mm ... 75 mm optional: 3 mm ... 35 mm	5 mm ... 75 mm optional: 3 mm ... 35 mm
Freie Apertur	28 mm	48 mm	48 mm	48 mm
EFL (effektive Brennweite)	+5 mm ... +500 mm -5 mm ... -450 mm	+5 mm ... +1.000 mm -5 mm ... -1.000 mm	+5 mm ... +1.500 mm -5 mm ... -1.200 mm	+5 mm ... +2.000 mm -5 mm ... -1.500 mm
Messbereich BFL und Radius	±5 mm ... ±490 mm	±5 mm ... ±490 mm	±5 mm ... ±690 mm	±5 mm ... ±1.000 mm
MTF	absolute MTF-Prüfung: 5 mm ... 50 mm EFL	absolute MTF-Prüfung: 5 mm ... 50 mm EFL	absolute MTF-Prüfung: 5 mm ... 50 mm EFL	absolute MTF-Prüfung: 5 mm ... 50 mm EFL